

Product Data Sheet


GW44221





Range 44 CE - Surface-mounting waterthight junction boxes in compilance with EN 60670-1 (CEI 23-48) and IEC 60670-22 (CEI 23-94) and made in high-performance technopolymers. The range includes versions with protection degree IP44, IP55, IP56 with smooth walls or with quick entry cable glands and different type of covers: blind / transparent, deep/plain, press-on/screw (in plastic, also 1/4 turn, or in metal). Available in different self-extinguishing materials (up to GWT 960 °C). Suitable for ordinary junctions, for special uses, and for industrial uses.

| BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS | | | | | | | | | | |
|--|--------------------------------------|-----------|--------------|-----------|--------------------------------------|------------------|------------------|--------------------------------------|--------------------------------------|--------------------------------------|
| Saline solution | Acids | | Bases | | Solvents | | | | Mineral | UV |
| | Concentrated | Diluited | Concentrated | Diluited | Hexane | Benzol | Acetone | Alcohol | oil | rays |
| Resistant | L <mark>imite</mark> d resistance | Resistant | Resistant | Resistant | L <mark>imite</mark> d resistance | Not resistant | Not resistant | L <mark>imite</mark> d resistance | L <mark>imite</mark> d resistance | L <mark>imite</mark> d resistance |

DIMENSIONAL







TECHNICAL SYMBOLOGY STANDARDS/APPROVALS



